



# BONA MEGA

## Product Description

Mega is a one-component non-toxic waterborne polyurethane timber floor finish. Mega uses oxygen in the air as a natural crosslinker to improve scratch and scuff resistance. The use of an external crosslinker is only necessary when re-coating previously finished floors. When coating bare timber it is recommended that Mega be used in conjunction with a sealer coat such as Prime or Seal. Mega is available in 3 gloss levels - matt, satin and gloss and is recommended for high traffic domestic areas such as kitchens and family rooms.

### Features

- 100% polyurethane formula
- Good wear resistance
- Non-toxic with low odour
- Non-yellowing
- Fast drying
- Non-flammable
- Superb natural finish in 3 gloss levels
- Suitable for re-coating most finishes
- Minimises edge-bonding when used with Prime
- Slip resistant AS/NZS 4586:1999

### Technical Data

Type of finish:	1-component waterborne 100% polyurethane oxygen crosslinking finish
Solids content:	Approx. 33%
Viscosity:	17 sec. (25°C, FC4)
pH-value:	Approx. 7.7
Resistance to wear:	Approx. 5 mg/100 revolutions (SIS 923509)
Density:	Finish 1.04 kg/dm <sup>3</sup>
Sheen (at 60°):	Gloss: Approx, 90, Silk matt: 45-50, Matt: 25-30
Drying time:	2-3 hours at 20°C / 60% R.H.
Application tools:	Roller or Bona applicator
Application rate:	8-10 m <sup>2</sup> /litre per coat
Safety:	Unclassified
Flash point:	Non-flammable
Shelf life:	At least 1 year, from the date of production, in unopened original container
Storage / transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Pack size:	5 litres and 1 litre



Bringing out The Best in Timber Floors  
Phone: 1800 626 001