



BONA TRAFFIC

Product Description

Traffic is a two-component non-toxic waterborne polyurethane timber floor finish with excellent resistance to wear. Traffic is recommended for high traffic domestic and commercial areas such as restaurants and retail outlets. Traffic is available in 2 gloss levels - Satin and a special Matt look called 'Invisible Protection' (IP) which highlights the natural beauty of the timber without distracting shine and reflections. Traffic is suitable for re-coating most existing surfaces including pre-finished timber. When coating bare timber it is recommended that Traffic be used in conjunction with a sealer coat such as Prime or Seal.

Features

- 100% polyurethane
- Excellent wear resistance
- Non-toxic - low odour
- Non-yellowing
- Non-flammable
- Fast drying
- Suitable for re-coating most finishes
- Natural Satin or Matt (IP) sheen
- Minimises edge-bonding when used with Prime
- Slip resistant AS/NZS 4586:1999

Technical Data

Type of finish:	2-component waterborne 100% polyurethane finish
Solids content:	Approx. 34%
Viscosity:	Approx. 24 sec. (25°C, FC4)
pH-value:	Approx. 8
Resistance to wear:	Approx. 2.5 mg/100 revolutions (SIS 923509)
Density:	Finish 1.05 kg/dm ³ , hardener 1.09 kg/dm ³
Sheen (at 60°):	Invisible Protection: ca. 15, Satin: ca. 45
Mixing ratio:	1 part Traffic Hardener to 9 parts Traffic
Pot life:	4 hours
Drying time:	3-4 hours at 20°C / 60% R.H.
Application tools:	Roller or Bona applicator
Application rate:	8-10 m ² /litre per coat
Safety:	Finish: Unclassified Hardener: Classified (see the Safety Data Sheet)
Flash point:	Non-flammable
Shelf life:	At least 1 year, from the date of production, in unopened original container
Storage / transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Pack size (inc. Hardener):	4.95 litres



Bringing out The Best in Timber Floors
Phone: 1800 626 001